



Precision Measuring Instruments

www.insizeus.com

FactoryLink
50 FREE FLYERS
PERSONALIZED

factorylink.com

YOUR COMPANY LOGO & CONTACT HERE

SALES SUPPORT & SERVICE
(740) 392-0330

ELECTRONIC CALIPERS (STANDARD TYPE)



1108-150

DATA OUTPUT
INSPECTION CERTIFICATE
TRACEABLE TO NIST

Part No.	Range	Accuracy	Price (\$)
1108-150	0-6"/0-150mm	±.0010"	68.30
1108-200	0-8"/0-200mm	±.0015"	101.00
1108-300	0-12"/0-300mm	±.0015"	152.00

- Resolution .0005"/0.01mm
- Buttons: on/off, zero, inch/mm
- Automatic power off, move the digital unit to turn on power
- Battery CR2032, data output
- Made of stainless steel
- Optional accessory: data output cable (part no. 7315-21, 7302-21)

DIAL CALIPERS



1311-6


SHOCK PROOF
INSPECTION CERTIFICATE
TRACEABLE TO NIST

- Dial indicator graduation .001"
- Shockproof dial indicator
- Made of stainless steel

Part No.	Range	Accuracy	Price (\$)
1311-6	0-6"	±.0015"	68.00
1311-8	0-8"	±.0020"	90.30
1311-12	0-12"	±.0020"	159.00

WATERPROOF ELECTRONIC OUTSIDE MICROMETERS (WITH DATA OUTPUT)

- Resolution .00005"/0.001mm
- Button function: on/off, set, inch/mm, ABS/INC
- IP65 dust/waterproof
- Data output
- Automatic power off
- Carbide measuring faces
- Ratchet stop
- Supplied with spherical anvil
- Setting standards are included (except 0-1"/0-25mm)
- Optional accessory: data output cable (part no. 7315-30, 7302-30)



3101-25E

INSPECTION CERTIFICATE
TRACEABLE TO NIST

DATA OUTPUT
ATTENTION: NO DATA OUTPUT

IP65
WATERPROOF

Part No.	Range	Accuracy	Price (\$)
3101-25E	0-1"/0-25mm	±.00010"	218.00

sizes available up to 12"

OUTSIDE MICROMETERS



3203-2A

- Graduation .0001"
- Carbide measuring faces
- Ratchet stop type
- Supplied with setting standards (except 0-1")

INSPECTION CERTIFICATE
TRACEABLE TO NIST

Part No.	Range	Accuracy	Price (\$)
3203-1A	0-1"	.00015"	43.70
3203-2A	1-2"	.00015"	48.80

Set

Part No.	Range	Micrometers included	Packaging	Price (\$)
3203-33A	0-3"	3203-1A, 3203-2A, 3203-3A	blow mould case	129.00
3203-66A	0-6"	3203-1A, 3203-2A, 3203-3A, 3203-4A, 3203-5A, 3203-6A	blow mould case	334.00
3203-1212A	0-12"	3203-1A, 3203-2A, 3203-3A, 3203-4A, 3203-5A, 3203-6A, 3203-7A, 3203-8A, 3203-9A, 3203-10A, 3203-11A, 3203-12A	aluminum box	951.00

*Micrometers up to 6" are supplied with inspection certificate


ELECTRONIC INDICATORS (ADVANCED TYPE)

- Meet ASME B89.1.10M-2001
- Reading in digital and analog
- Display can be rotated by 320°
- Button function: tolerance Go and No-Go display, data preset, measuring direction change, max./min./TIR measurement, inch/metric conversion, absolute/incremental measurement
- Keep preset data and tolerance data in memory after restart
- CR2032 battery, automatic power off
- Data output
- Optional accessory: data output cable (part no. 7315-50M, 7302-40M, 7305-40M), backs, contact points



2103-10E

DATA OUTPUT
INSPECTION CERTIFICATE
TRACEABLE TO NIST



Part No.	Range	Accuracy	Resolution	Hysteresis	Remark	Price (\$)
2103-10E	.5"/12.7mm	±.00015"	.00005"/0.001mm	.00005"	lug back	423.00
2103-25E	1"/25.4mm	±.00015"	.00005"/0.001mm	.00005"	lug back	471.00
2103-50E	2"/50.8mm	±.00015"	.00005"/0.001mm	.00005"	lug back	757.00

WiFi DIGITAL MEASURING MICROSCOPE PART NO. ISM-WF200

- Maximum working distance is 200" under WiFi mode
- Can be connected to multiple iPads, Android devices or computers at the same time under WiFi mode
- Take pictures and videos
- Supplied with software



stand (part no.: ISM-WSTD, optional)



SPECIFICATION

Price (\$)	444.00
Magnification	10X~200X
Pixel	1.3M (resolution: 1280x1024)
Illumination	built-in adjustable LED
Power supply	built-in rechargeable battery

MAGNIFICATION, FOCUS DISTANCE, VIEW FIELD AND ACCURACY

Magnification	Focus distance	View field	Accuracy
50X	.83"	.32x.25"	1.2mil
100X	.51"	.15x.12"	0.6mil
150X	.63"	.10x.08"	0.4mil
200X	.75"	.07x.06"	0.3mil



Precision Measuring Instruments
www.insizeus.com

NEW Training Center!

